



Marca: UNITECH

Modelo: MR650



Características

- ↻ Sistema operativo Windows CE 5.0 Professional
- ↻ Amplia pantalla táctil de 5.6" TFT color QVGA 240 x 320
- ↻ Camara de fotos integrada de 1.3 megapixel
- ↻ Varios modelos, Con lector de codigos de barras, magnético o de proximidad.
- ↻ Slot CF para comunicación wireless
- ↻ Slot SD para expansión de memoria
- ↻ Speaker audio output
- ↻ Microphone audio input
- ↻ 3 Relay para control de dispositivos externos (barreras, semaforo, etc)
- ↻ 4 Entrada digital
- ↻ 1 Puertos RS232
- ↻ Batería de respaldo de hasta 2 horas de operación y/o 3 días de backup de datos
- ↻ 1 año de garantía

Terminal color. Moderno diseño. Camara de fotos integrada

Terminal 100 % programable, robusta, versátil, diseñada para satisfacer los requerimientos más sofisticados de control de asistencia, acceso y trabajo en línea.

Puede configurarse en red tanto cableada como wireless, permitiendo aplicaciones complejas.

Posee una camara integrada para aplicaciones de control de acceso o kiosko interactivo.

Posee conectividad ethernet integrada, interface RS232, relays y entradas TTL.



SCREEN CHECK

Innovate today with the vision of tomorrow

Especificaciones técnicas

System

OS	Windows CE 5.0 Professional
CPU	Intel PXA270 @ 520MHz
RAM	128MB
FlashROM	64MB
Keyboard	6 hard keys, Clock In (F1), Clock Out (F2), Break In (F3), Break Out (F4), Enter (Yes), Escape (No)
Display	5.6" TFT- LCD QVGA (240x320) color

Multimedia Features

Camera	1.3 mega pixel CMOS camera
Audio Output	0.8W Speaker
Microphone Input	

Power Management

Power Input	12 VDC
UPS	One rechargeable Lithium-Ion battery pack @ 3.8V, 4000mAh
UPS Operating Time	2 hours operation and 3 days data backup

Communication and I/O

Interface	1 RS232 port
Output	3 Relays, 4 TTL Digital inputs
Ethernet Connection	RJ45, Power-over-Ethernet (optional)

Expansion

CF type II card slot for Wireless 802.11b/g	
SD slot for memory	
Barcode Input	Symbologies supported, China Postal Code, Codabar, Code 11, Code 32, Code 39, Code 93, Code 128, Delta Code, Interleaved 2 of 5, ISBT 128, Lable Code IV, Lable Code V, MSI, Standard 2 of 5, Toshiba Code, UPC/EAN
Magnetic Stripe Reader	Triple track MSR reader
Proximity Reader	EM, 125 kHz, HID, 125 kHz
Fingerprint Reader	Sensor Authentec AFS8500
	Verification time, Maximum 2 seconds
	Equal Error Rate 0.1% at medium security
	Number of Templates 4000

Software Programming Tools

Embedded Visual Basic terminal program for T&A	
Embedded Visual C++ terminal program for T&A	

Physical and Environmental

Operating Temperature	32°F to 122°F (0°C to 50°C)
Storage Temperature	-4°F to 158°F (-20°C to 70°C)
Humidity	5% to 95% RH non-condensing